



### **0KLK030.T Information**



For Reference Only

Part Number 0KLK030.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 30A 600VAC/500VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0KLK030.T Specifications**

| Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  5AG, 10mm x 38.1mm  Series  POWR-GARD? KLK  Fuse Type  Cartridge  Current Rating  30A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  O.406" Dia x 1.500" L (10.31mm x 38.10mm)  |                                   |   |     |
|--|-----------------------------------|---|-----|
| Category  Circuit Protection  Electrical, Specialty Fuses  Package  5AG, 10mm x 38.1mm  Series  POWR-GARD? KLK  Fuse Type  Cartridge  Current Rating  30A  Voltage Rating - AC  600V  Voltage Rating - DC  500V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  5ize / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  Features  - CB, CSA, QPL, UL  Operating Temperature  For the Capacity @ Rated Voltage  Holder  Package / Case  5AG, 10mm x 38.1mm  0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Manufacturer Part Number          | 0KLK030.T                                 |     |
| Flectrical, Specialty Fuses  Package  5AG, 10mm x 38.1mm  Series  POWR-GARD? KLK  Fuse Type  Cartridge  Current Rating  30A  Voltage Rating - AC  600V  Voltage Rating - DC  500V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  Fines SAG, 10mm x 38.10mm)  Fines SAG, 10mm x 38.10mm  Size / Dimension  Capacity SAG, 10mm x 38.10mm  O.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Manufacturer                      | Littelfuse Inc.                           |     |
| Package5AG, 10mm x 38.1mmSeriesPOWR-GARD? KLKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Category                          | Circuit Protection                        |     |
| SeriesPOWR-GARD? KLKFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)   |                                   | Electrical, Specialty Fuses               |     |
| Fuse Type Current Rating 30A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Canon Carridge A00V Converting C | Package                           | 5AG, 10mm x 38.1mm                        |     |
| Current Rating  Voltage Rating - AC  600V  Voltage Rating - DC  500V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  30A  30A  30A  400V  30A  400V  400V | Series                            | POWR-GARD? KLK                            |     |
| Voltage Rating - AC  Voltage Rating - DC  500V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  600V | Fuse Type                         | Cartridge                                 |     |
| Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, QPL, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  500V  Fast Fast Fast Fast Fast Flow Flow Flow Flow Flow Flow Flow Flow   | Current Rating                    | 30A                                       |     |
| Response Time Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial - Lectrical, Ind | Voltage Rating - AC               | 600V                                      |     |
| Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Voltage Rating - DC               | 500V                                      |     |
| Features - Class - Class - CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Response Time                     | Fast                                      |     |
| Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Applications                      | Electrical, Industrial                    |     |
| Approvals  CE, CSA, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Features                          | -   |     |
| Operating Temperature  Breaking Capacity @ Rated Voltage  100kA AC, 50kA DC  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Class                             | -   |     |
| Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Approvals                         | CE, CSA, QPL, UL                          |     |
| Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)  | Operating Temperature             | -   |     |
| Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Breaking Capacity @ Rated Voltage | 100kA AC, 50kA DC                         |     |
| Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)   | Mounting Type                     | Holder                                    |     |
| · · · · · ·  | Package / Case                    | 5AG, 10mm x 38.1mm                        |     |
| Report errors?   | Size / Dimension                  | 0.406" Dia x 1.500" L (10.31mm x 38.10mm) |     |
| Report circles:  |                                   | Report error                              | rs? |

### **0KLK030.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0KLK030.T Payment Methods**



















# **0KLK030.T Shipping Methods**













If you have any question about 0KLK030.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com