



### **0LDC150.X Information**

Heisener.com

For Reference Only

Part NumberOLDC150.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 150A 600VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LDC150.X Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD?, POWR-PRO? LDC  Fuse Type  Cartridge  Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Features  -  Class  L  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Littelfuse Inc.  Circuit Protection  Electrical, Specialty Fuses  Cylindrical, Blade Terminal (Bolt)  Electrical, Specialty Fuses  Footnote  Solar (Photov-Province)  Electrical, Specialty Fuses  Cartridge  Ca	•	
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  POWR-GARD?, POWR-PRO? LDC  Fuse Type  Cartridge  Current Rating  150A  Voltage Rating - AC  600V  Voltage Rating - DC  Response Time  Applications  Solar (Photovoltaic)  Features  Class  L  Approvals  Operating Temperature	Manufacturer Part Number	0LDC150.X
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series POWR-GARD?, POWR-PRO? LDC  Fuse Type Cartridge  Current Rating 150A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class L  Approvals CE, CSA, UL  Operating Temperature -	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? LDC  Fuse Type Cartridge Current Rating 150A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L Approvals CE, CSA, UL Operating Temperature -	Category	Circuit Protection
Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 150A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L Approvals CE, CSA, UL Operating Temperature -		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 150A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class L  Approvals CE, CSA, UL  Operating Temperature -	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 150A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Solar (Photovoltaic)  Features -  Class L  Approvals CE, CSA, UL  Operating Temperature -	Series	POWR-GARD?, POWR-PRO? LDC
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Applications  Solar (Photovoltaic)  Features  -  Class  L  Approvals  CE, CSA, UL  Operating Temperature  600V  East  Fast  Clove  Color  CLOR  CE, CSA, UL  COLOR  CE, CSA, UL  COLOR	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class L  Approvals CE, CSA, UL  Operating Temperature -	Current Rating	150A
Response Time Fast Applications Solar (Photovoltaic) Features - Class L Approvals CE, CSA, UL Operating Temperature -	Voltage Rating - AC	600V
Applications Solar (Photovoltaic)  Features - Class L Approvals CE, CSA, UL Operating Temperature -	Voltage Rating - DC	600V
Features - Class L Approvals CE, CSA, UL Operating Temperature -	Response Time	Fast
Class L Approvals CE, CSA, UL Operating Temperature -	Applications	Solar (Photovoltaic)
Approvals CE, CSA, UL Operating Temperature -	Features	-
Operating Temperature -	Class	L
	Approvals	CE, CSA, UL
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC	Operating Temperature	-
The state of the s	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC
Mounting Type Bolt Mount	Mounting Type	Bolt Mount
Package / Case Cylindrical, Blade Terminal (Bolt)	Package / Case	Cylindrical, Blade Terminal (Bolt)
Size / Dimension 2.500" Dia x 3.752" L (63.50mm x 95.30mm)	Size / Dimension	2.500" Dia x 3.752" L (63.50mm x 95.30mm)
Report errors		Report errors?

### **0LDC150.X Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0LDC150.X Payment Methods**



















## **0LDC150.X Shipping Methods**













If you have any question about 0LDC150.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com