



0LDC1800X Information

Heisener.com

Part NumberOLDC1800XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 1.8KA 600VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LDC1800X Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC Voltage Rating - DC Response Time Applications Solar (Photovoltaic) Features Class L
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class L
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Series POWR-GARD?, POWR-PRO? LDC Fuse Type Cartridge Current Rating 1.8kA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Fuse Type Current Rating 1.8kA Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Current Rating 1.8kA Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class 600V Fast Solar (Photovoltaic) - Class
Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Response Time Fast Applications Solar (Photovoltaic) Features - Class L
Applications Solar (Photovoltaic) Features - Class L
Features - Class L
Class
Approvals CE CSA III
Approvals CE, CSA, UL
Operating Temperature -
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC
Mounting Type Bolt Mount
Package / Case Cylindrical, Blade Terminal (Bolt)
Size / Dimension 3.500" Dia x 3.752" L (88.90mm x 95.30mm)
Report errors

0LDC1800X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LDC1800X Payment Methods





















0LDC1800X Shipping Methods













If you have any question about 0LDC1800X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com