



## **0LGR005.U Information**

Heisener.com

Part Number0LGR005.UManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 5A 300VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LGR005.U Specifications**

Manufacturer Part Number       OLGR005.U         Manufacturer       Littelfuse Inc.         Category       Circuit Protection         Electrical, Specialty Fuses         Package       Cartridge, Non-Standard         Series       POWR-GARD? LGR         Fuse Type       Cartridge         Current Rating       5A         Voltage Rating - AC       300V         Voltage Rating - DC       -         Response Time       Fast         Applications       Electrical, Industrial         Features       -         Class       -         Approvals       CE, CSA, UL         Operating Temperature       -         Breaking Capacity @ Rated Voltage       10kA         Mounting Type       Holder         Package / Case       Cartridge, Non-Standard         Size / Dimension       0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  POWR-GARD? LGR  Fuse Type  Cartridge  Current Rating  5A  Voltage Rating - AC  300V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Holder  Package / Case  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  For CE, CSA, UL  Operating Temperature  For CE, CSA, UL  Operating Temperature  For Cartridge, Non-Standard  Octor Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LGR005.U
Beaking Capacity @ Rated Voltage  Flectrical, Specialty Fuses  Cartridge, Non-Standard  POWR-GARD? LGR  POWR-GARD? LGR  Cartridge  Current Rating  5A  Voltage Rating - AC  300V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Electrical, Specialty Fuses  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
Series POWR-GARD? LGR  Fuse Type Cartridge  Current Rating 5A  Voltage Rating - AC 300V  Voltage Rating - DC -  Response Time Fast  Applications Electrical, Industrial  Features -  Class -  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 5A Voltage Rating - AC Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension  CARCA CA	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  300V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  5A  300V  - CE, CSA  - CRA  Fast  Fast  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPERATION CAPACITY OF CAPAC	Series	POWR-GARD? LGR
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300V  - CR  Fast  - CR  Fast  Fast  Clectrical, Industrial  - CE, CSA, UL	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  Fast  Cattridge, Non-Standard  0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Current Rating	5A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial  CE, CSA, UL  - CE, CSA, UL  CE, CSA,	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - CSA, UL  Approvals CE, CSA, UL  Operating Temperature - IOKA  Breaking Capacity @ Rated Voltage IOKA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
*		Report errors?

### **0LGR005.U Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0LGR005.U Payment Methods**





















## **0LGR005.U Shipping Methods**













If you have any question about 0LGR005.U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com