



## **0LGR005.V Information**

Manufacturer Littelfuse Inc. Category Heisener.com

Part Number 0LGR005.V

Circuit Protection

Electrical, Specialty Fuses **Description** FUSE CARTRIDGE 5A 300VAC IN LINE

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LGR005.V Specifications**

Manufacturer Part Number     OLGR005.V       Manufacturer     Littelfuse Inc.       Category     Circuit Protection       Electrical, Specialty Fuses       Package     In-Line       Series     POWR-GARD? LGR       Fuse Type     Cartridge       Current Rating     5A       Voltage Rating - AC     300V       Voltage Rating - DC     -       Response Time     Fast       Applications     Electrical, Industrial       Features     -       Class     -       Approvals     CE, CSA, UL       Operating Temperature     -       Breaking Capacity @ Rated Voltage     10kA       Mounting Type     Wire Lead       Package / Case     In-Line       Size / Dimension     0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  In-Line  Series  POWR-GARD? LGR  Fuse Type  Cartridge  Current Rating  5A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  In-Line  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  In-Line  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  In-Line  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  In-Line  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  In-Line  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Size / Dimension  Cartridge  Cartridg	Manufacturer Part Number	0LGR005.V
Beaking Capacity @ Rated Voltage  Fleetrical, Specialty Fuses  In-Line  Flow T-GARD? LGR  POWR-GARD? LGR  Fuse Type  Cartridge  Current Rating  5A  Voltage Rating - AC  300V  Voltage Rating - DC  - Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension	Manufacturer	Littelfuse Inc.
PackageIn-LineSeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 5A Voltage Rating - AC Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Vire Lead Package / Case Size / Dimension  Canon Cartridge Save Save Save Save Save Save Save Sav	Package	In-Line
Current Rating  Voltage Rating - AC  300V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  5A  300V  - CE, CSA, UL  - Class  - Cletrical, Industrial  Electrical, Industrial  Electrical, Industrial  Features  - CE, CSA, UL  - CE, CSA, UL  Operating Temperature  In-Line  O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Series	POWR-GARD? LGR
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  300V  - CE, CSA, UL  - URA  Signor Dia x 1.820" L (15.49mm x 46.23mm)	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead  Package / Case Size / Dimension  Fast  Fast Fast Fast Fast Fast Fast Fa	Current Rating	5A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension  Fast Fast Fast Fast Fast Fast Fast Float Flo	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension  CE, CSA, UL  Wire Lead 10kA Wire Lead Under Lead 10kA Vire Lead Voltage	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension  0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line  Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
· · · · · ·	Package / Case	In-Line
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
*		Report errors?

#### **0LGR005.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0LGR005.V Payment Methods**





















## **0LGR005.V Shipping Methods**













If you have any question about 0LGR005.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com