



0LGR009.H Information

Heisener.com

For Reference Only

Part Number OLGR009.H
Manufacturer Littelfuse Inc.
Category Circuit Protec

Circuit Protection Electrical, Specialty Fuses

Description FUSE CARTRIDGE 9A 300VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LGR009.H Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? LGR Fuse Type Cartridge Current Rating 9A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Octor of Time Accarted Acca		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? LGR Fuse Type Cartridge Current Rating 9A Voltage Rating - AC 300V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Features - Cartridge, Non-Standard Cartridge, Non-Standard Ocion Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LGR009.H
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cartridge, Non-Standard POWR-GARD? LGR POWR-GARD? LGR Cartridge Current Rating 9A Voltage Rating - AC 300V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses POWR-GARD? LGR And And Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating9AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 9A Voltage Rating - AC 300V Voltage Rating - DC	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 300V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 9A 300V - CE, CSA - CRA Fast Fast CE, CSA - CE	Series	POWR-GARD? LGR
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V - CE, CSA, UL - CE, CSA	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Catridge, Non-Standard O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Current Rating	9A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CE, CSA, UL - OPERATOR OF THE PROPERTY OF TH	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - Case Cartridge, Non-Standard Size / Dimension - Class - Case	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

0LGR009.H Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LGR009.H Payment Methods



















0LGR009.H Shipping Methods













If you have any question about 0LGR009.H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com