



0LGR010.V Information

Heisener.com

Part NumberOLGR010.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 10A 300VAC IN LINE

Package In-Line

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LGR010.V Specifications

Manufacturer Part NumberOLGR010.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LGR010.V
Package In-Line Series POWR-GARD? LGR Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 300V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension IGR SWR-GARD? LGR POWR-GARD? LGR P	Manufacturer	Littelfuse Inc.
Package In-Line Series POWR-GARD? LGR Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 300V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LGRFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC300VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	In-Line
Current Rating Voltage Rating - AC 300V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension 10A 10A 10A 10A 10A 10A 10A 10A 10A 10	Series	POWR-GARD? LGR
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension 300V - CE, CSA, UL - Class - CE, CSA, UL - CE, CSA, U	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension - Response Time Fast Fast Fast Fast Fast Fast Fast Fast	Current Rating	10A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension Fast Electrical, Industrial Cec, CSA, UL CE, CSA, UL VER CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage In-Line Size / Dimension O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension CE, CSA, UL Wire Lead 10kA Wire Lead 10h	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
· · · · · · · · · · · · · · · · · · ·	Package / Case	In-Line
	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
Report errors?		Report errors?

0LGR010.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LGR010.V Payment Methods



















0LGR010.V Shipping Methods













If you have any question about 0LGR010.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com