



0LKN150.V Information

Part Number 0LKN150.V Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE LINK 150A 250VAC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LKN150.V Specifications

Manufacturer Part Number OLKN150.V Manufacturer Littelfuse Inc. Category Circuit Protection Package Cylindrical, Blade Terminals Series POWR-GARD? LKN Fuse Type Fuse Link Current Rating 150A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? LKNFuse TypeFuse LinkCurrent Rating150AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Manufacturer Part Number	0LKN150.V
Beckrical, Specialty Fuses Cylindrical, Blade Terminals Series POWR-GARD? LKN Fuse Type Fuse Link Current Rating 150A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension I.563" Dia x 4.378" L (39.70mm x 111.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? LKNFuse TypeFuse LinkCurrent Rating150AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Category	Circuit Protection
Series POWR-GARD? LKN Fuse Type Fuse Link Current Rating 150A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 150A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fuse Link Fuse Fuse Fuse Fuse Fuse Fuse Fuse Fuse	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 250V Voltage Rating - DC	Series	POWR-GARD? LKN
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Holder Package / Case Size / Dimension 250V CHOOK CONTROL CON	Fuse Type	Fuse Link
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class Lectrical, Industrial	Current Rating	150A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial - Lectrical, Industrial Lectrical,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Voltage Rating - DC	-
Features - Class H Approvals CE, CSA, UL Operating Temperature - I0kA Breaking Capacity @ Rated Voltage Holder Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, UL - CRACK	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 1.563" Dia x 4.378" L (39.70mm x 111.20mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.563" Dia x 4.378" L (39.70mm x 111.20mm)
		Report errors?

0LKN150.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LKN150.V Payment Methods


































If you have any question about 0LKN150.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com