

# 0LKS006.S

# **0LKS006.S Information**



Part Number	0LKS006.S	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE LINK 6A 600VAC NON STD	
Package	Cartridge, Non-Standard	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **0LKS006.S Specifications**

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating6AVoltage Rating - AC60VVoltage Rating - DCFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature0KAMounting TypeHolderPackage / CaseSartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHOperating TemperatureSc, CSA, ULOperating TypeIokAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / DimensionSal'l" Diax 3.748" L (20.60mm x 95.20mm)	Manufacturer Part Number	0LKS006.S
Bit of the section o	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Type-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)		Electrical, Specialty Fuses
Fuse TypeFuse LinkCurrent Rating6AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated VoltageHolderMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / DimensionSal' "Diax 3.748" L (20.60mm x 95.20mm)	Package	Cartridge, Non-Standard
Current Rating6AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811"Dia x 3.748" L (20.60mm x 95.20mm)	Series	POWR-GARD? LKS
Voltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Fuse Type	Fuse Link
Voltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Current Rating	6A
Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Voltage Rating - DC	-
Features-Features-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Response Time	Fast
ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Class	Н
Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.748" L (20.60mm x 95.20mm)
		Report errors?

### **0LKS006.S** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0LKS006.S Payment Methods**



# **0LKS006.S Shipping Methods**



If you have any question about 0LKS006.S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com