

## **0LKS008.S Information**

Heisener.com

Part Number OLKS008.S

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE LINK 8A 600VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LKS008.S Specifications**

Manufacturer Part NumberOLKS008.SManufacturerLittelfuse Inc.CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Manufacturer Part Number	0LKS008.S
PackageElectrical, Specialty FusesSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating8AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 8A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fuse Link  8A  A  Bruse Link  8A  CE, CSA  Fast  Fast  Cavrridge, Non-Standard  Size / Dimension  Fuse Link  8A  A  A  A  Bout  CE  Cavrridge, Non-Standard  Size / Dimension  Size / Dimension  Fuse Link  8A  A  A  A  CE  Cavrridge, Non-Standard  Size / Dimension  Size / Dimension	Package	Cartridge, Non-Standard
Current Rating 8A  Voltage Rating - AC 600V  Voltage Rating - DC -  Response Time Fast  Applications Electrical, Industrial  Features -  Class H  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Series	POWR-GARD? LKS
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  H  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  60	Fuse Type	Fuse Link
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class H  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  - Cattridge, Non-Standard Size / Dimension  - Size / Dimension  - CE, CSA, UL  COPITATION OF TABLET	Current Rating	8A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial  CE, CSA, UL  - CE, C	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Voltage Rating - DC	-
Features - Class H  Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.748" L (20.60mm x 95.20mm)
		Report errors?

### **0LKS008.S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0LKS008.S Payment Methods**





















## **0LKS008.S Shipping Methods**













If you have any question about 0LKS008.S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com