

0LKS025.S Information

Heisener.com

For Reference Only

Part NumberOLKS025.SManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE LINK 25A 600VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LKS025.S Specifications

Manufacturer Part Number OLKS025.S Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? LKS Fuse Type Fuse Link Current Rating 25A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)		
Category Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? LKS Fuse Type Fuse Link Current Rating 25A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cirridge, Non-Standard Size / Dimension Cirridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	0LKS025.S
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating25AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.748" L (20.60mm x 95.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 25A Voltage Rating - AC 600V Voltage Rating - DC	Package	Cartridge, Non-Standard
Current Rating Current Rating 25A Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 25A 600V C	Series	POWR-GARD? LKS
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Fuse Link
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Catridge, Non-Standard 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Current Rating	25A
Response Time Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial Features - CR, CSA, UL CE, C	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Voltage Rating - DC	-
Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.811" Dia x 3.748" L (20.60mm x 95.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.748" L (20.60mm x 95.20mm)
•		Report errors?

0LKS025.S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LKS025.S Payment Methods





















0LKS025.S Shipping Methods













If you have any question about 0LKS025.S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com