

### **0LMF.500V Information**

( Heisener.com

For Reference Only

Part NumberOLMF.500VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 500MA 300VAC INLINE

Package In-Line

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0LMF.500V Specifications**

Manufacturer Part NumberOLMF.500VManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating500mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating500mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LMF.500V
Package In-Line Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 500mA Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension   Delevance In-Line Size / Dimension   Delevance In-Line Size / Dimension   Down Response In-Line Size / Dimension   Dimension   Dimension   Dimension   Source ARD POWR-GARD V Fuses POWR-GARD? Fuses Size / Dimension   Dimension   Source ARD PowR-GARD? Fuses Size / Dimension   Source ARD PowR-Gard PowR-GARD? Size / Dimension   Source ARD PowR-Gard PowR-GARD? Size / Dimension   Source ARD PowR-GARD? Size / Dimension   Source ARD PowR-Gard PowR-GARD? Size / Dimension   Source ARD PowR-Gard PowR-GARD? Size / Dimension   Source ARD PowR-GARD	Manufacturer	Littelfuse Inc.
Package         In-Line           Series         POWR-GARD? LMF           Fuse Type         Cartridge           Current Rating         500mA           Voltage Rating - AC         300V           Voltage Rating - DC         -           Response Time         Slow           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Wire Lead           Package / Case         In-Line           Size / Dimension         0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating500mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating500mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	In-Line
Current Rating 500mA  Voltage Rating - AC 300V  Voltage Rating - DC -  Response Time Slow  Applications Electrical, Industrial  Features -  Class -  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line  Size / Dimension 5000000000000000000000000000000000000	Series	POWR-GARD? LMF
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  300V  300V  300V  CE, CSA, UL  - Class  - Class  - CE, CSA, UL  - CE, CSA, UL	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow  Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead  Package / Case Size / Dimension - Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	500mA
Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension  Slow  Slow	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - Class - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension  CE, CSA, UL  Wire Lead 10kA  Wire Lead 10h	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line  Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
· · · · · · · · · · · · · · · · · · ·	Package / Case	In-Line
	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
Report errors?		Report errors?

#### **0LMF.500V Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0LMF.500V Payment Methods**





















### **0LMF.500V Shipping Methods**













If you have any question about 0LMF.500V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com