

0LMF.800U Information

Heisener.com

Part Number OLMF.800U

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 800MA 300VAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LMF.800U Specifications

Manufacturer Part NumberOLMF.800UManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LMF.800U
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	Cartridge, Non-Standard
Current Rating 800mA Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 800mA 800m 800m	Series	POWR-GARD? LMF
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V CE, CSA, UL - Class - Catrridge, Non-Standard 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Clectrical, Industrial - CE, CSA, UL CE,	Current Rating	800mA
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial CE, CSA, UL - CE, CSA, UL CE, CSA,	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - CR CSA, UL CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

0LMF.800U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LMF.800U Payment Methods



















0LMF.800U Shipping Methods













If you have any question about 0LMF.800U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com