

0LMF.800V Information

Heisener.com

Part Number OLMF.800V
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 800MA 300VAC INLINE

Package In-Line

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0LMF.800V Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package In-Line Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses Littelfuse Inc. Circuit Protection Electrical, Industrial Features - CE, CSA, UL Operating Temperature In-Line Size / Dimension O.610" Dia x 1.820" L (15.49mm x 46.23mm)		
Category Circuit Protection Electrical, Specialty Fuses Package In-Line Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC 300V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage In-Line Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical	Manufacturer Part Number	0LMF.800V
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses In-Line PoWR-GARD? LMF Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension	Manufacturer	Littelfuse Inc.
PackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating800mAVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 800mA Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 800mA Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension Current Rating 800mA 800mA 800mA 800m CE, CSA, UL Class - Where Lead In-Line Size / Dimension Cartridge Siow Ann Ann Ann Ann Ann Ann Ann Ann Ann An	Package	In-Line
Current Rating Voltage Rating - AC 300V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension 800mA 800m 10kA 800mA 800m - 10kA 800mA 800m 10kA 800mA 800m 10kA 800mA 800m 10kA 800m 10kA 800m 10kA 801m 801m	Series	POWR-GARD? LMF
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension 300V - CR CONTINUE Slow Clectrical, Industrial CE, CSA, UL - CONTINUE CONTI	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case Size / Dimension - Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	800mA
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension Slow Electrical, Industrial - CE, CSA, UL OPERATOR OF CE, CSA, UL Wire Lead OPERATOR OF COMMENT	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - CE, CSA, UL CE, CSA, UL Operating Temperature - IOkA Wire Lead Package / Case In-Line Size / Dimension - O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension CE, CSA, UL - UL 10kA Wire Lead UL 10kA Wire Lead UL 10kA 1	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
·	Package / Case	In-Line
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

0LMF.800V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LMF.800V Payment Methods



















0LMF.800V Shipping Methods













If you have any question about 0LMF.800V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com