

### **0LMF02.8V Information**

Heisener.com

For Reference Only

Part Number 0LMF02.8V
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 2.8A 300VAC IN LINE

Package In-Line

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LMF02.8V Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc.  Category  Circuit Protection  Electrical, Specialty Fuses  Package  In-Line  Series  POWR-GARD? LMF  Fuse Type  Cartridge  Current Rating  2.8A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  In-Line  Size / Dimension  Littelfuse Inc.  Circuit Protection  Electrical, Specialty Fuses  Littelfuse Inc.  Circuit Protection  Electrical, Industrial  CE, CSA, UL  Operating Temperature  In-Line  Size / Dimension  O.610" Dia x 1.820" L (15.49mm x 46.23mm)		
Category Circuit Protection Electrical, Specialty Fuses  In-Line Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 2.8A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension  In-Line  Circuit Protection Electrical, Specialty Fuses  In-Line Electrical, Industrial Features - Class - Circuit Protection Electrical, Industrial Features - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage In-Line Size / Dimension  Circuit Protection  Electrical, Industrial Features - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage In-Line Size / Dimension	Manufacturer Part Number	0LMF02.8V
Beaking Capacity @ Rated Voltage  Electrical, Specialty Fuses  In-Line  PoWR-GARD? LMF  Fuse Type  Cartridge  Current Rating  2.8A  Voltage Rating - AC  300V  Voltage Rating - DC  -  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension	Manufacturer	Littelfuse Inc.
PackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating2.8AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 2.8A Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 2.8A Voltage Rating - AC 300V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension  Cass Cartridge 2.8A Cartridge 2.8A CE, CSA, UL Columnation CE, CSA, UL Col	Package	In-Line
Current Rating  Voltage Rating - AC  300V  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  2.8A  300V  - CE, CSA, UL  - CE, CSA, UL  Vire Lead  In-Line  Size / Dimension  0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Series	POWR-GARD? LMF
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  Size / Dimension  300V  - CR  CONTINUE  Slow  Clectrical, Industrial  CE, CSA, UL  - CONTINUE  CONTI	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow  Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead  Package / Case Size / Dimension - Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	2.8A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Wire Lead Package / Case In-Line Size / Dimension Slow Electrical, Industrial - CE, CSA, UL  OPERATOR OF CE, CSA, UL  Wire Lead OPERATOR OF COMMENT	Voltage Rating - AC	300V
Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - CE, CSA, UL CE, CSA, UL Operating Temperature - IOkA Wire Lead Package / Case In-Line Size / Dimension - O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension  CE, CSA, UL  -  UL  10kA  Wire Lead  UL  10kA  Wire Lead  UL  10kA  1	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Wire Lead  Package / Case  In-Line  Size / Dimension  0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Wire Lead  Package / Case In-Line  Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Wire Lead Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
·	Package / Case	In-Line
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

#### **0LMF02.8V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0LMF02.8V Payment Methods**





















### **0LMF02.8V Shipping Methods**













If you have any question about 0LMF02.8V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com