



0LMF1.25UXL Information

Heisener.com

Part Number 0LMF1.25UXL
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 1.25A 300VAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









		~ •••	
0LMF1.	.25UXL	Specific	cations

Manufacturer Part NumberOLMF1.25UXLManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LMF1.25UXL
Package Cartridge, Non-Standard Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 1.25A Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension (Cartridge, Non-Standard (Size / Dimension)) Features (Cartridge, Non-Standard (Size / Dimension)) Features (Cartridge, Non-Standard (Size / Dimension))	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? LMF Fuse Type Cartridge Current Rating 1.25A Voltage Rating - AC 300V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 300V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1.25A 1.25A 1.25A 1.25A 1.25A 1.25A 1.25A 1.25A 1.26A 1.2	Series	POWR-GARD? LMF
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 300V 300V 300V CE, CSA, UL - Class - Catrridge, Non-Standard O.610" Dia x 1.820" L (15.49mm x 46.23mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class - CE, CSA, UL COPITATION COPIT	Current Rating	1.25A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial CE, CSA, UL - CE, CSA, UL CE, CSA,	Voltage Rating - AC	300V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features - Class - CR CSA, UL CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

0LMF1.25UXL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0LMF1.25UXL Payment Methods



















0LMF1.25UXL Shipping Methods













If you have any question about 0LMF1.25UXL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com