

# 0LMF1.25V

## **0LMF1.25V Information**

Heisener.com	Part Number Manufacturer Category Description Package	0LMF1.25V Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses FUSE CRTRDGE 1.25A 300VAC INLINE In-Line For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **0LMF1.25V** Specifications

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated VoltageIbkAMounting TypeVire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
CategoryCircuit ProtectionCategoryCircuit ProtectionElectrical, Specialty FusesPackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LMF1.25V
BitElectrical, Specialty FusesPackageIn-LinePackagePOWR-GARD? LMFSeriesCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating TemperatureIokABreaking Capacity @ Rated VoltageIokAPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer	Littelfuse Inc.
PackageIn-LineSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / Case0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
Power-GARD? LMF   Series POWR-GARD? LMF   Fuse Type Cartridge   Current Rating 1.25A   Voltage Rating - AC 300V   Voltage Rating - DC -   Response Time Slow   Applications Electrical, Industrial   Features -   Class -   Approvals CE, CSA, UL   Operating Type -   Breaking Capacity @ Rated Voltage INA   Mounting Type Mire Lead   Package / Case In-Line   Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature10kABreaking Capacity @ Rated VoltageNive LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	In-Line
Current Rating1.25ACurrent Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Series	POWR-GARD? LMF
Voltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Current Rating	1.25A
Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - AC	300V
ApplicationsElectrical, IndustrialApplications-Features-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage10kAMounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting TypeWire LeadPackage / CaseIn-LineSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / Case In-Line Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Wire Lead
	Package / Case	In-Line
Report error?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
Report criois:		Report errors?

#### **0LMF1.25V** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 0LMF1.25V, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com