

0NLN002.T Information

Heisener.com

For Reference Only

Part Number0NLN002.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 2A 250VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLN002.T Specifications

Manufacturer Part NumberONLN002.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Circuit Protection Electrical, Specialty Fuses Electridge Circuit Protection Electridge Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Industrial Features - CLass K5 Approvals CE, CSA, UL Operating Temperature Freaking Capacity @ Rated Voltage Holder Cartridge, Non-Standard Size / Dimension O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer Part Number	0NLN002.T
Flectrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 2A Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses POWR-GARD? NLN Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses PowR-GARD? NLN Lattridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage SokA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 2A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Casov Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Capacity @ Capa	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 2A 250V 250V CE, CSA CE, CSA Electrical, Industrial CE, CSA CE, CSA CE, CSA CE, CSA CE, CSA CE, CSA CON CE, CSA CON CON CON CON CON CON CON CO	Series	POWR-GARD? NLN
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 250V 250V 250V Electrical, Industrial - Cletrical, Industrial - CE, CSA, UL - CE, CSA, U	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V Electrical, Industrial CE, CSA, UL COPITATION OF TABLE OF TAB	Current Rating	2A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CE, CSA, UL CE, CSA, UL - CE, C	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	250V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL Holder Cartridge, Voltage Cartridge, Non-Standard O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
· · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

0NLN002.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLN002.T Payment Methods





















0NLN002.T Shipping Methods













If you have any question about 0NLN002.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com