



ONLN060.T Information

Heisener.com

For Reference Only

Part Number0NLN060.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 60A 250VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLN060.T Specifications

Manufacturer Part Number ONLN060.T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial Four CE, CSA, UL CE, CSA, UL Operating Temperature Four CE, CSA, UL Operating Temperature Four CE, CSA, UL Operating Temperature Four CE, CSA, UL Operating Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	0NLN060.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage SokA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Category	Circuit Protection
Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 60A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 60A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cass Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension COA Cartridge C	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 60A 60A 60A 60A 60A 60A 60A 60	Series	POWR-GARD? NLN
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 250V 250V 250V Electrical, Industrial - Clectrical, Industrial - CE, CSA, UL - CE, CSA,	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V East Six	Current Rating	60A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CE, CSA, UL C	Voltage Rating - AC	250V
Applications Features - Class K5 Approvals Ce, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Industrial - Router - Cartridge, Non-Standard 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - DC	250V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Fracking Capacity @ Rated Voltage S0kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CRACK OF AC, 20kA DC Holder Holder Cartridge, Non-Standard 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.000" L (20.60mm x 76.20mm)
•		Report errors?

0NLN060.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLN060.T Payment Methods



















0NLN060.T Shipping Methods













If you have any question about 0NLN060.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com