

0NLN250.X Information

Heisener.com

Part Number 0NLN250.X Manufacturer Littelfuse Inc. Category

Electrical, Specialty Fuses

Circuit Protection

Description FUSE CARTRIDGE 250A 250VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLN250.X Specifications

Manufacturer Part Number ONLN250.X Manufacturer Littelfuse Inc. Category Circuit Protection Package Cylindrical, Blade Terminals Series POWR-GARD? NLN Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Manufacturer Part Number	0NLN250.X
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cylindrical, Blade Terminals POWR-GARD? NLN Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Fuse Trime Fast Cylindrical, Blade Terminals Size / Dimension Electrical, Fuse Trime Cylindrical, Blade Terminals Size / Dimension Electrical, Fuse Trime Cylindrical, Blade Terminals Size / Dimension Cylindrical, Blade Terminals Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 250A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Capacity @ Cartridge Capacity @ Cartridge Capacity @ Cartridge Capacity & Cartridge Capacity & Cartridge Capacity & Cartridge Capacity & Ca	Package	Cylindrical, Blade Terminals
Current Rating 250A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 250V	Series	POWR-GARD? NLN
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V CE, CSA Fast Fast CE, CSA, UL COPITATION OF COMMENT O	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 250V 2600 East Fast CE, CSA, UL - C	Current Rating	250A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial CE, CSA, UL - Holder - CE, CSA, UL - CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Voltage Rating - DC	250V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - SokA Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.094" Dia x 4.878" L (53.19mm x 123.90mm)
		Report errors?

0NLN250.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLN250.X Payment Methods



















0NLN250.X Shipping Methods













If you have any question about 0NLN250.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com