

ONLN350.X Information

(A) Heisener.com

Part Number0NLN350.XManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 350A 250VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLN350.X Specifications

Manufacturer Part NumberONLN350.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Manufacturer Part Number	0NLN350.X
PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating350AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Package	Cylindrical, Blade Terminals
Current Rating 350A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 250V	Series	POWR-GARD? NLN
Voltage Rating - AC Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V CE, CSA Fast Fast Ce, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COJundrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V East Fast Fast CE, CSA CE, CSA, UL CE, CSA, UL CUIndrical, Blade Terminals CUIndrical, Blade Terminals CUINDRICAL (53.19mm x 123.90mm)	Current Rating	350A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial CE, CSA, UL - Holder - CE, CSA, UL - CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Voltage Rating - DC	250V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - SokA Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, UL CHARACTERIST SIZE / SI	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 2.094" Dia x 4.878" L (53.19mm x 123.90mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.094" Dia x 4.878" L (53.19mm x 123.90mm)
		Report errors?

0NLN350.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLN350.X Payment Methods



















0NLN350.X Shipping Methods













If you have any question about 0NLN350.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com