

### **0NLS035.T Information**

Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 35A 600VAC/400VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com

Part Number 0NLS035.T



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0NLS035.T Specifications**

Manufacturer Part Number  Manufacturer  Littelfuse Inc. Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD? NLS  Fuse Type  Cartridge  Current Rating  35A  Voltage Rating - AC  600V  Voltage Rating - DC  400V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  NLS035.T  Littelfuse Inc.  Circuit Protection  Electrical, Specialty Fuses  Cartridge  Non-Standard  Store (27.00mm x 139.70mm)  Report errors?		
Category Circuit Protection Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 35A Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Token AC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	0NLS035.T
Bectrical, Specialty Fuses  Cartridge, Non-Standard  POWR-GARD? NLS  Fuse Type Cartridge Current Rating 35A  Voltage Rating - AC 600V  Voltage Rating - DC 400V  Response Time Fast Applications Electrical, Industrial  Features - Class K5  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension  Electrical, Industrial Features - CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERTING Temperature Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses Solva AC, 20kA DC CE, CSA, UL Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Solva Sol	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard  Series POWR-GARD? NLS  Fuse Type Cartridge  Current Rating 35A  Voltage Rating - AC 600V  Voltage Rating - DC 400V  Response Time Fast  Applications Electrical, Industrial  Features -  Class K5  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage SokA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Category	Circuit Protection
Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 35A Voltage Rating - AC 600V Voltage Rating - DC 400V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 35A Voltage Rating - AC 600V Voltage Rating - DC 400V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Cov 600V  400V  Electrical, Industrial  - CE, CSA, UL  CE, CSA, UL  COPIE Holder Cartridge, Non-Standard Size / Dimension  Cartridge, Non-Standard  1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 400V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  35A 600V  400V  400V  CE, CSA  400V  CE, CSA  CE, CSA  LO  CE, CSA  CE, C	Series	POWR-GARD? NLS
Voltage Rating - AC  Voltage Rating - DC  400V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class K5  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  400V  400V  400V  400V  400V  400V  400V  400  Fast  Fast  Clectrical, Industrial  -  CE, CSA, UL  - CE,	Current Rating	35A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial - CE, CSA, UL - CE, CSA	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Voltage Rating - DC	400V
Features - Class K5  Approvals CE, CSA, UL  Operating Temperature - Freaking Capacity @ Rated Voltage 50kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 5.500" L (27.00mm x 139.70mm)
		Report errors?

#### **0NLS035.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0NLS035.T Payment Methods**



















### **0NLS035.T Shipping Methods**













If you have any question about ONLS035.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com