

0NLS040.T Information

Heisener.com

For Reference Only

Part NumberONLS040.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 40A 600VAC/400VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLS040.T Specifications

Manufacturer Part NumberONLS040.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)Report errors?		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Manufacturer Part Number	0NLS040.T
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC400VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Package	Cartridge, Non-Standard
Current Rating 40A Voltage Rating - AC 600V Voltage Rating - DC 400V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Series	POWR-GARD? NLS
Voltage Rating - AC Voltage Rating - DC 400V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 400V East 400V Autous 500 Electrical, Industrial - CE, CSA, UL - CE,	Current Rating	40A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UL CE, CSA,	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Voltage Rating - DC	400V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - SokA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 1.063" Dia x 5.500" L (27.00mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.063" Dia x 5.500" L (27.00mm x 139.70mm)
		Report errors?

0NLS040.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLS040.T Payment Methods



















0NLS040.T Shipping Methods













If you have any question about ONLS040.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com