

0NLS070.V Information

Manufacturer Littelfuse Inc. Category Heisener.com

Part Number 0NLS070.V

Circuit Protection Electrical, Specialty Fuses

Description FUSE CARTRIDGE 70A 600VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0NLS070.V Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminals POWR-GARD? NLS Fuse Type Current Rating 70A Voltage Rating - AC Voltage Rating - DC Response Time Applications Features Class Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses Cylindrical, Blade Terminals POWR-GARD? NLS Cartridge Current Rating 70A 600V 600V Features Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder	•	
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 70A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Cylindrical, Specialty Fuses Electrical, Blade Terminals Electridge Cartridge Cartridge 600V Food Cartridge 600V Food Cartridge Cartridge Food Food Cartridge Cartridge Food F	Manufacturer Part Number	0NLS070.V
Electrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 70A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Holder Electrical, Specialty Fuses Cartridge Cartridge 600V Foundable CE, CSA, UL Operating Temperature Foundable Foundable	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminals Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 70A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Category	Circuit Protection
Series POWR-GARD? NLS Fuse Type Cartridge Current Rating 70A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder		Electrical, Specialty Fuses
Fuse Type Current Rating 70A Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Cartridge Cartridge 70A CHOWN FOR ACTOM TO A	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 600V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type 70A 600V Fast CE, CSA, UL Holder	Series	POWR-GARD? NLS
Voltage Rating - AC Voltage Rating - DC 600V Response Time Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type 600V 600V Fast CE, CSA, UL 600V Fast CE, CSA, UL For CSA, UL Holder	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type 600V 600V 600V 600V Fast Fast Clectrical, Industrial - CE, CSA, UL Holder	Current Rating	70A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Fast Fast Fast Fast Fost Floating Claustrial Features - Holder	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Voltage Rating - DC	600V
Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type CE, CSA, UL Holder	Features	-
Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Class	K5
Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder	Approvals	CE, CSA, UL
Mounting Type Holder	Operating Temperature	-
- 1-	Breaking Capacity @ Rated Voltage	50kA
	Mounting Type	Holder
Package / Case Cylindrical, Blade Terminals	Package / Case	Cylindrical, Blade Terminals
Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Size / Dimension	1.311" Dia x 5.874" L (33.30mm x 149.20mm)
Report errors		Report errors?

0NLS070.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0NLS070.V Payment Methods



















0NLS070.V Shipping Methods













If you have any question about ONLS070.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com