

### **0NLS090.V Information**

Manufacti Category

**Part Number** 0NLS090.V **Manufacturer** Littelfuse Inc.

Circuit Protection Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 90A 600VAC/VDC

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0NLS090.V Specifications**

Manufacturer Part Number         ONLS090.V           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Package         Cylindrical, Blade Terminals           Series         POWR-GARD? NLS           Fuse Type         Cartridge           Current Rating         90A           Voltage Rating - AC         600V           Voltage Rating - DC         600V           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         K5           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         50kA           Mounting Type         Holder           Package / Case         Cylindrical, Blade Terminals           Size / Dimension         1.311" Dia x 5.874" L (33.30mm x 149.20mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Manufacturer Part Number	0NLS090.V
PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLSFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.874" L (33.30mm x 149.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating90AVoltage Rating - AC600VVoltage Rating - DC600VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Package	Cylindrical, Blade Terminals
Current Rating 90A  Voltage Rating - AC 600V  Voltage Rating - DC 600V  Response Time Fast  Applications Electrical, Industrial  Features -  Class K5  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage 50kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Series	POWR-GARD? NLS
Voltage Rating - AC  Voltage Rating - DC  600V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  6	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class K5  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  600V  Fast  Fast  CE, CSA  Hounting Type Holder  Cylindrical, Blade Terminals  1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Current Rating	90A
Response Time Applications Electrical, Industrial  Features - Class K5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class K5  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 50kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Voltage Rating - DC	600V
Features - Class K5  Approvals CE, CSA, UL  Operating Temperature - SokA  Breaking Capacity @ Rated Voltage 50kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  50kA  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  50kA  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Breaking Capacity @ Rated Voltage	50kA
Size / Dimension 1.311" Dia x 5.874" L (33.30mm x 149.20mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.311" Dia x 5.874" L (33.30mm x 149.20mm)
		Report errors?

#### **0NLS090.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0NLS090.V Payment Methods**



















## **0NLS090.V Shipping Methods**













If you have any question about ONLS090.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com