



ORLN020.T Information

Heisener.com

For Reference Only

Part NumberORLN020.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 20A 250VAC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ORLN020.T Specifications

Manufacturer Part Number ORLN020.T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? RLN Fuse Type Cartridge Current Rating 20A Voltage Rating - AC 250V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? RLN Fuse Type Cartridge Current Rating 20A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage I Oka Mounting Type Holder Package / Case Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial For CE, CSA, UL Operating Temperature - CLass H Holder For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses For Cartridge, Non-Standard Size / Dimension Circuit Protection For Cartridge, Non-Standard For Cartri	Manufacturer Part Number	0RLN020.T
Beaking Capacity @ Rated Voltage Flectrical, Specialty Fuses Cartridge, Non-Standard POWR-GARD? RLN Fuse Type Cartridge Current Rating 20A Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses POWR-GARD? RLN Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? RLNFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? RLNFuse TypeCartridgeCurrent Rating20AVoltage Rating - AC250VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 20A Voltage Rating - AC 250V Voltage Rating - DC	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 20A 250V 250V 250V - 10A Fast Fast CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATION OF STANDARD CE, CSA, UL COPERATION OF STANDARD CE, CSA, UL COPERATION OF STANDARD COPERATION OF STANDARD CARTINGE, Non-Standard Size / Dimension CIASS OF Dia x 2.000" L (14.30mm x 50.80mm)	Series	POWR-GARD? RLN
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V 260V 600 Fast Fast Ce, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL CIANA CE, CSA, UL COPERATION OF COMMENT OF C	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cattridge, Non-Standard Size / Dimension - Size / Dimension - CE, CSA, UL CE, CS	Current Rating	20A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial CE, CSA, UL - CE, C	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	-
Features - Class H CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

ORLN020.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ORLN020.T Payment Methods





















ORLN020.T Shipping Methods













If you have any question about ORLN020.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com