

ORLS200.X Information

(A) Heisener.com

Part Number ORLS200.X

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 200A 600VAC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ORLS200.X Specifications

Manufacturer Part NumberORLS200.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Manufacturer Part Number	0RLS200.X
PackageCylindrical, Specialty FusesSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Category	Circuit Protection
SeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Package	Cylindrical, Blade Terminals
Current Rating 200A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Series	POWR-GARD? RLS
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Size / Dimension Fast CE, CSA, UL CE, CSA	Current Rating	200A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Voltage Rating - DC	-
Features - Class H Approvals CE, CSA, UL Operating Temperature - I0kA Breaking Capacity @ Rated Voltage Holder Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.843" Dia x 6.878" L (46.80mm x 174.70mm)
		Report errors?

ORLS200.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ORLS200.X Payment Methods



















ORLS200.X Shipping Methods













If you have any question about ORLS200.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com