

ORLS250.X Information

Part Number 0RLS250.X Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CRTRDGE 250A 600VAC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ORLS250.X Specifications

Manufacturer Part NumberORLS250.XManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.878" L (65.90mm x 200.10mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Manufacturer Part Number	0RLS250.X
Backage Cylindrical, Blade Terminals Series POWR-GARD? RLS Fuse Type Cartridge Current Rating 250A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? RLSFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.594" Dia x 7.878" L (65.90mm x 200.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 250A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Converting Capacity @ Rated Voltage Cartridge Cartridge Cartridge Converting Capacity @ Rated Voltage Cartridge Cartridge Converting Converting Capacity @ Rated Voltage Cylindrical, Blade Terminals Size / Dimension Cartridge Cartridge Capacity @ Capaci	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250A 600V - CR 600V - CE, CSA Fast CE, CSA, UL CE, CSA, UL CE, CSA, UL CYLINDERS OF TEMPERATURE CYLINDERS OF TEMPERATURE CYLINDERS OF TEMPERATURE 250A CUIT OF TEMPERATURE CUIT OF TEMPERATURE CYLINDERS	Series	POWR-GARD? RLS
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V - CR Fast Fast Fast CE, CSA, UL	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class CE, CSA, UL	Current Rating	250A
Response Time Applications Electrical, Industrial Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fast Electrical, Industrial CE, CSA, UL OPERATOR OF CE, CSA, UL CE, CSA,	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Voltage Rating - DC	-
Features - Class H Approvals CE, CSA, UL Operating Temperature - I0kA Breaking Capacity @ Rated Voltage Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, CSA, UL - CRACK	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 2.594" Dia x 7.878" L (65.90mm x 200.10mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	2.594" Dia x 7.878" L (65.90mm x 200.10mm)
		Report errors?

ORLS250.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0RLS250.X Payment Methods



















ORLS250.X Shipping Methods













If you have any question about ORLS250.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com