



OSLC005.T Information



For Reference Only

Part Number OSLC005.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 5A 600VAC/170VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0SLC005.T Specifications

Manufacturer Part Number Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? SLC Fuse Type Cartridge Current Rating 5A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class G Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Seport errors? Littelfuse Inc. Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard O,406" Dia x 1.311" L (10.30mm x 33.30mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? SLC Fuse Type Current Rating 5A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Circuit Protection Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	0SLC005.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard POWR-GARD? SLC Fuse Type Current Rating 5A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class G Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial Features - Cartridge, Non-Standard O.406" Dia x 1.311" L (10.30mm x 33.30mm)	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? SLC Fuse Type Cartridge Current Rating 5A Voltage Rating - AC 600V Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Category	Circuit Protection
Series POWR-GARD? SLC Fuse Type Cartridge Current Rating 5A Voltage Rating - AC 600V Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 5A Voltage Rating - AC Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Circh Cartridge, Non-Standard Size / Dimension Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Cartridge Cartridge, Non-Standard Ca	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5A 600V CE, CSA 600V Medium Addium Action Medium Action Medium Action Medium Action Medium Action Belectrical, Industrial CE, CSA, QPL, UL CE, CSA, QPL, UL CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Holder Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Series	POWR-GARD? SLC
Voltage Rating - AC Voltage Rating - DC Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V Medium Medium CE, CSA, Industrial - CB, CSA, QPL, UL - CE, CSA, QPL,	Current Rating	5A
Response Time Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Medium Medium Medium Medium Medium Medium Medium Medium Lectrical, Industrial - CE, CSA, QPL, UL - CE, CSA, QPL - CE, CSA, Q	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Voltage Rating - DC	170V
Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Response Time	Medium
Class Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension G CE, CSA, QPL, UL - CE, CSA, QPL - CE, CSA, QPL - CE, CSA, QPL - CE, CSA, QPL - CE, CSA, QPL	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Class	G
Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Breaking Capacity @ Rated Voltage	100kA AC, 10kA DC
Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.311" L (10.30mm x 33.30mm)
		Report errors?

OSLC005.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0SLC005.T Payment Methods



















0SLC005.T Shipping Methods













If you have any question about OSLC005.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com