



OSLC015.T Information



For Reference Only

Part Number OSLC015.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 15A 600VAC/170VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0SLC015.T Specifications

Manufacturer Part NumberOSLC015.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? SLCFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC600VVoltage Rating - DC170VResponse TimeMediumApplicationsElectrical, IndustrialFeatures-ClassGApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 10kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.311" L (10.30mm x 33.30mm)Report errors?		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? SLCFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC600VVoltage Rating - DC170VResponse TimeMediumApplicationsElectrical, IndustrialFeatures-ClassGApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 10kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Manufacturer Part Number	0SLC015.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? SLC Fuse Type Cartridge Current Rating 15A Voltage Rating - AC Voltage Rating - DC Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial Features - CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage ADOKA AC, 10kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension D 4.06° Dia x 1.311" L (10.30mm x 33.30mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? SLCFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC600VVoltage Rating - DC170VResponse TimeMediumApplicationsElectrical, IndustrialFeatures-ClassGApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 10kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Category	Circuit Protection
SeriesPOWR-GARD? SLCFuse TypeCartridgeCurrent Rating15AVoltage Rating - AC600VVoltage Rating - DC170VResponse TimeMediumApplicationsElectrical, IndustrialFeatures-ClassGApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 10kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.406" Dia x 1.311" L (10.30mm x 33.30mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 15A Voltage Rating - AC 600V Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Non-Standard Size / Dimension Cartridge C	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 15A 600V 170V Response Time Medium CE, CSA, QPL 100kA AC, Industrial 100kA AC, 10kA DC	Series	POWR-GARD? SLC
Voltage Rating - AC Voltage Rating - DC 170V Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V Medium Cle, CSA, QPL, UL CT, CSA, QPL, UL CE, CSA, QPL, UL COPICATION COPICATIO	Current Rating	15A
Response Time Medium Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Voltage Rating - DC	170V
Features - Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Response Time	Medium
Class G Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Class	G
Breaking Capacity @ Rated Voltage 100kA AC, 10kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Breaking Capacity @ Rated Voltage	100kA AC, 10kA DC
Size / Dimension 0.406" Dia x 1.311" L (10.30mm x 33.30mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.406" Dia x 1.311" L (10.30mm x 33.30mm)
		Report errors?

OSLC015.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0SLC015.T Payment Methods



















0SLC015.T Shipping Methods













If you have any question about OSLC015.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com