



#### **OSPF003.HXR Information**



For Reference Only

Part Number OSPF003.HXR
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 3A 1KVDC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0SPF003.HXR Specifications**

Manufacturer Part Number         OSPF003.HXR           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         3A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         PCB           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)   Report errors?		
Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         3A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         PCB           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0SPF003.HXR
Flectrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         3A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         PCB           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         3A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         PCB           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         3A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         PCB           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating3AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypePCBPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC  Voltage Rating - DC  Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals Cperating Temperature Breaking Capacity @ Rated Voltage Mounting Type PCB Package / Case Size / Dimension  3A  A  A  A  B  A  A  B  A  B  A  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  A  B  B	Series	POWR-GARD? SPF
Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type PCB  Package / Case Size / Dimension  - 1000V (1kV)  Capacity (1000	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage  Mounting Type PCB  Package / Case Size / Dimension  1000V (1kV) Fast CE, CSA CH CPHOTOVOLTAIC CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATE CE, CSA, UL CE, CSA, UL COPERATE CE, CSA, UL CE, CSA	Current Rating	3A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Solar (Photovoltaic) Feat CR CP, CSA, UL CE, CSA, UL CE	Voltage Rating - AC	-
Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	1000V (1kV)
Features - Class - Class - CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  20kA  Mounting Type  PCB  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA  Mounting Type PCB  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	PCB
· · · · · · · · · · · · · · · · · · ·	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

#### **0SPF003.HXR Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0SPF003.HXR Payment Methods**





















### **0SPF003.HXR Shipping Methods**













If you have any question about 0SPF003.HXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com