



0SPF020.HXR Information



For Reference Only

Part Number OSPF020.HXR
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 20A 1KVDC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0SPF020.HXR Specifications

Manufacturer Part Number OSPF020.HXR Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? SPF Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? SPF Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0SPF020.HXR
Package 5AG, 10mm x 38.1mm Series POWR-GARD? SPF Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series POWR-GARD? SPF Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series POWR-GARD? SPF Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 20A Voltage Rating - AC - Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension 20A 1000V (1kV) - Solar (Photovoltaic) Fast Solar (Photovoltaic) - CE, CSA, UL - CE, CSA, UL - CB, CSA, UL - CB	Series	POWR-GARD? SPF
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type PCB Package / Case Size / Dimension - 1000V (1kV) - 1000V (1kV) Collection Fast Collection - 1000V (1kV) -	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type PCB Package / Case Size / Dimension 1000V (1kV) Fast CE, CSA CH CPHOTOVOLTAIC CE, CSA, UL CE, CSA, UL CE, CSA, UL COPERATE CE, CSA, UL CE, CSA, UL COPERATE CE, CSA, UL CE, CSA	Current Rating	20A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Solar (Photovoltaic) Feat CR CP, CSA, UL CE, CSA, UL CE	Voltage Rating - AC	-
Applications Solar (Photovoltaic) Features - Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, CSA, UL CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, CSA, UL
Mounting Type PCB Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	PCB
· · · · · · · · · · · · · · · · · · ·	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

0SPF020.HXR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0SPF020.HXR Payment Methods





















0SPF020.HXR Shipping Methods













If you have any question about 0SPF020.HXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com