



#### **0SPF025.H Information**



For Reference Only

Part NumberOSPF025.HManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 25A 1KVDC 5AG

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0SPF025.H Specifications**

Manufacturer Part Number         OSPF025.H           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL, VDE           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)   Report errors?		
Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL, VDE           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0SPF025.H
Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL, VDE           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL, VDE           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series         POWR-GARD? SPF           Fuse Type         Cartridge           Current Rating         25A           Voltage Rating - AC         -           Voltage Rating - DC         1000V (1kV)           Response Time         Fast           Applications         Solar (Photovoltaic)           Features         -           Class         -           Approvals         CE, CSA, UL, VDE           Operating Temperature         -           Breaking Capacity @ Rated Voltage         20kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating25AVoltage Rating - AC-Voltage Rating - DC1000V (1kV)Response TimeFastApplicationsSolar (Photovoltaic)Features-Class-ApprovalsCE, CSA, UL, VDEOperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating  Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  25A  1000V (1kV)  Fast  CE, CSA, UL, VDE  CE, CSA, UL, VDE  404  404  404  404  404  405  406  406	Series	POWR-GARD? SPF
Voltage Rating - AC  Voltage Rating - DC  1000V (1kV)  Response Time  Fast  Applications  Solar (Photovoltaic)  Features  - Class  - Approvals  CE, CSA, UL, VDE  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  - 1000V (1kV)  CE, CSA  Fast  - 4000	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL, VDE  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  1000V (1kV) Fast CE, CSA CHOOTO CONTROL CONT	Current Rating	25A
Response Time Applications Solar (Photovoltaic) Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Solar (Photovoltaic) Feat CR, CSA, UL, VDE	Voltage Rating - AC	-
Applications Solar (Photovoltaic)  Features - Class - Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	1000V (1kV)
Features - Class - CE, CSA, UL, VDE  Operating Temperature - Cexample Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 20kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Solar (Photovoltaic)
Approvals CE, CSA, UL, VDE Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 20kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, CSA, UL, VDE
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	20kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

#### **0SPF025.H Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **0SPF025.H Payment Methods**



















### **0SPF025.H Shipping Methods**













If you have any question about 0SPF025.H, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com