



0TLN005.T Information

Heisener.com

Part Number 0TLN005.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 5A 170VDC NON STD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0TLN005.T Specifications

Manufacturer Part Number OTLN005.T Manufacturer Littelfuse Inc. Category Circuit Protection Package Cartridge, Non-Standard Series POWR-GARD? TLN Fuse Type Cartridge Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer Part Number	0TLN005.T
Electrical, Specialty Fuses Package Cartridge, Non-Standard Series POWR-GARD? TLN Fuse Type Cartridge Current Rating SA Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Fown-Standard Cartridge, Non-Standard Size / Dimension Eattrical, Specialty Fuses Cartridge, Non-Standard Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard Series POWR-GARD? TLN Fuse Type Cartridge Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating5AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Cartridge Cartridge, Non-Standard Size / Dimension Cartridge Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension	Package	Cartridge, Non-Standard
Current Rating 5A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 5A 100V 100V 100V 100V 100V 100V 100V 100C 10	Series	POWR-GARD? TLN
Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class - Cartridge, Non-Standard Size / Dimension - Control Operating Temperature Cartridge, Non-Standard Size / Dimension - Control Operating Temperature Cartridge, Non-Standard Cartridge, Cartridge, Cartridge, Cartridge, Cartridge, Cartridge,	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V Fast Fast Fast Ce, UR - 100kA Holder Cartridge, Non-Standard Size / Dimension 170V Fast 170V 170V 170V 170V 1804 1804 1805	Current Rating	5A
Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Telecom - Helcom	Voltage Rating - DC	170V
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

0TLN005.T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0TLN005.T Payment Methods



















0TLN005.T Shipping Methods













If you have any question about 0TLN005.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com