



OTLN080.V Information

Manufact
Category

Part Number 0TLN080.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 80A 170VDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0TLN080.V Specifications

Manufacturer Part NumberOTLN080.VManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 3.748" L (27.00mm x 95.20mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Manufacturer Part Number	0TLN080.V
Beckrical, Specialty Fuses Package Cylindrical, Blade Terminals Series POWR-GARD? TLN Fuse Type Cartridge Current Rating 80A Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminals Size / Dimension POWR-GARD? TLN Cartridge Cartridge Cartridge POWR-GARD? TLN Features Cartridge Cartridge Four Cartridge Cartrid	Manufacturer	Littelfuse Inc.
Package Cylindrical, Blade Terminals Series POWR-GARD? TLN Fuse Type Cartridge Current Rating 80A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 3.748" L (27.00mm x 95.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Package	Cylindrical, Blade Terminals
Current Rating Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 80A 80A 80A 80A 80A 80A 80A 80	Series	POWR-GARD? TLN
Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - 170V Fast - 170V Cass Features Fast Cecom CE, UR CE, UR COPITATION ON A Holder Holder For Cylindrical, Blade Terminals 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Fuse Type	Cartridge
Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Current Rating	80A
Response Time Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension Fast Telecom Cless - CL, UR CE, UR - Breaking Capacity @ Rated Voltage Holder Holder Fackage / Case Cylindrical, Blade Terminals 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension Telecom - Class - Cultant - CE, UR - CE, UR - CE, UR - CE, UR - CUR -	Voltage Rating - DC	170V
Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 1.063" Dia x 3.748" L (27.00mm x 95.20mm)	Mounting Type	Holder
` '	Package / Case	Cylindrical, Blade Terminals
	Size / Dimension	1.063" Dia x 3.748" L (27.00mm x 95.20mm)
Report errors?		Report errors?

0TLN080.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0TLN080.V Payment Methods





















0TLN080.V Shipping Methods













If you have any question about 0TLN080.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com