

0TLN250.X Information

Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CRTRDGE 250A 170VDC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

Part Number 0TLN250.X

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0TLN250.X Specifications

| Manufacturer Part Number OTLN250.X Manufacturer Littelfuse Inc. Category Circuit Protection Beckage Cylindrical, Blade Terminals Series POWR-GARD? TLN Fuse Type Cartridge Current Rating 250A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | | |
|--|-----------------------------------|--|
| CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Manufacturer Part Number | 0TLN250.X |
| PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Manufacturer | Littelfuse Inc. |
| PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Category | Circuit Protection |
| SeriesPOWR-GARD? TLNFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.752" L (53.19mm x 120.70mm) | | Electrical, Specialty Fuses |
| Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Package | Cylindrical, Blade Terminals |
| Current Rating 250A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 250A | Series | POWR-GARD? TLN |
| Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V 17 | Fuse Type | Cartridge |
| Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 170V Fast Fast Fast Fast CLe, UR - 100kA Holder Cylindrical, Blade Terminals Size / Dimension 170V Fast Fast Fast Fast Fast Fast Fast Fas | Current Rating | 250A |
| Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Voltage Rating - AC | - |
| Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension Telecom Telecom Telecom Telecom Telecom Featom Featom CE, UR Operating Temperature - Holder CE, UR CE, UR CUR Featom CE, UR CE, UR CUR CE, UR CUR CE, UR CE, UR CUR CUR CUR CUR CUR CUR CUR | Voltage Rating - DC | 170V |
| Features - Class - Class - CE, UR Approvals CE, UR Operating Temperature - CE, UR Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Response Time | Fast |
| Class - Approvals CE, UR Operating Temperature - Grace Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Applications | Telecom |
| Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Holder Package / Case Cylindrical, Blade Terminals Size / Dimension CE, UR CHANCE CUR CUR CUR CUR CUR CUR CUR C | Features | - |
| Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Class | - |
| Breaking Capacity @ Rated Voltage 100kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Approvals | CE, UR |
| Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Operating Temperature | - |
| Package / Case Cylindrical, Blade Terminals Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Breaking Capacity @ Rated Voltage | 100kA |
| Size / Dimension 2.094" Dia x 4.752" L (53.19mm x 120.70mm) | Mounting Type | Holder |
| | Package / Case | Cylindrical, Blade Terminals |
| Report errors? | Size / Dimension | 2.094" Dia x 4.752" L (53.19mm x 120.70mm) |
| | | Report errors? |

0TLN250.X Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0TLN250.X Payment Methods



















0TLN250.X Shipping Methods













If you have any question about 0TLN250.X, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com