



# **0TLS002.TXV Information**

Manuf Catego

Part Number0TLS002.TXVManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 2A 170VDC RAD BEND

Package Radial Bend Cylinder

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0TLS002.TXV Specifications**

Manufacturer Part NumberOTLS002.TXVManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.563" Dia x 0.877" H (14.30mm x 22.28mm)Report errors?		
CategoryCircuit ProtectionFlectrical, Specialty FusesPackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Manufacturer Part Number	0TLS002.TXV
Package Radial Bend Cylinder Series POWR-GARD? TLS Fuse Type Cartridge Current Rating 2A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension Electrical, Specialty Fuses Radial Bend Cylinder Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Manufacturer	Littelfuse Inc.
PackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.563" Dia x 0.877" H (14.30mm x 22.28mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating2AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Package	Radial Bend Cylinder
Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Package / Case  Size / Dimension  2A  170V  170V  170V  1810  1800  Feats  Fast  Telecom  Telecom  CE, UR  CE, UR  100kA  100kA  Mounting Type  Radial Bend Cylinder  Size / Dimension  1.563" Dia x 0.877" H (14.30mm x 22.28mm)	Series	POWR-GARD? TLS
Voltage Rating - AC  Voltage Rating - DC  170V  Response Time Fast  Applications Telecom  Features - Class - Approvals  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension  - Response Time Fast Fast Fast  Cle, UR  CE, UR  100kA  Mounting Type Through Hole Radial Bend Cylinder Size / Dimension  - Size / Dimension  - Size / Dimension	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Telecom  Features - Class - Approvals Ce, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension  170V  170V  170V  170V  1804  100K  100K	Current Rating	2A
Response Time Fast  Applications Telecom  Features - Class - Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 100kA  Mounting Type Through Hole  Package / Case Radial Bend Cylinder  Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension  Telecom - Cleom - Theodem - Though Hole Radial Bend Cylinder 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Voltage Rating - DC	170V
Features - Class - Class - CE, UR  Operating Temperature - Capacity @ Rated Voltage 100kA  Mounting Type Through Hole  Package / Case Radial Bend Cylinder  Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Through Hole  Package / Case  Radial Bend Cylinder  Size / Dimension  0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Through Hole  Package / Case Radial Bend Cylinder  Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Approvals	CE, UR
Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Operating Temperature	-
Package / Case Radial Bend Cylinder Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.563" Dia x 0.877" H (14.30mm x 22.28mm)	Mounting Type	Through Hole
	Package / Case	Radial Bend Cylinder
Report errors?	Size / Dimension	0.563" Dia x 0.877" H (14.30mm x 22.28mm)
		Report errors?

### **0TLS002.TXV Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **0TLS002.TXV** Payment Methods





















### **0TLS002.TXV Shipping Methods**













If you have any question about 0TLS002.TXV, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com