



0TLS010.TXL Information

Heisener.com

Part Number 0TLS010.TXL
Manufacturer Littelfuse Inc.
Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 10A 170VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0TLS010.TXL Specifications

Manufacturer Part Number OTL S010.TXL Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? TLS Fuse Type Cartridge Current Rating 10A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Manufacturer Part Number	0TLS010.TXL
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? TLS Fuse Type Cartridge Current Rating 10A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 100kA	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating10AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.740" L (14.30mm x 44.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 10A 10A 10A 10A 10A 10A 10A 10A 10A 10	Series	POWR-GARD? TLS
Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Control	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals Ce, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 170V 170V 170V 1800 180	Current Rating	10A
Response Time Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Telecom Ce, UR CE, UR CE, UR COBA Bolt Mount CE, UR COBA Bolt Mount CE, UR COBA COBA Bolt Mount COBA Bolt Mount Coba Cylindrical, Blade Terminal (Bolt)	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Telecom - CE, UR - C	Voltage Rating - DC	170V
Features - Class - Class - CE, UR Operating Temperature - Cextra Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.563" Dia x 1.740" L (14.30mm x 44.20mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.563" Dia x 1.740" L (14.30mm x 44.20mm)
±		Report errors?

0TLS010.TXL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0TLS010.TXL Payment Methods



















0TLS010.TXL Shipping Methods













If you have any question about 0TLS010.TXL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com