



OTLS040.TXLS Information

Heisener.com

Part NumberOTLS040.TXLSManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 40A 170VDC RAD BEND

Package Radial Bend Cylinder

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0TLS040.TXLS Specifications

Manufacturer Part Number OTLS040.TXLS Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package Radial Bend Cylinder Series POWR-GARD? TLS Fuse Type Cartridge Current Rating 40A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Manufacturer Part Number	0TLS040.TXLS
PackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Manufacturer	Littelfuse Inc.
PackageRadial Bend CylinderSeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeThrough HolePackage / CaseRadial Bend CylinderSize / Dimension0.562" Dia x 0.944" L (14.28mm x 23.98mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 40A Voltage Rating - AC - Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Package	Radial Bend Cylinder
Current Rating Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals Ce, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 40A 40A 40A 40A 40A 40A 40A 40	Series	POWR-GARD? TLS
Voltage Rating - AC Voltage Rating - DC 170V Response Time Fast Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension - Size / Dimension Fast 170V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Telecom Features - Class - Approvals Ce, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Size / Dimension 170V Fast 170V 170V 1800 1	Current Rating	40A
Response Time Fast Applications Telecom Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension Telecom - Theodom CE, UR Through Hole 100kA Through Hole Package / Case Radial Bend Cylinder 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Voltage Rating - DC	170V
Features - Class - Class - CE, UR Operating Temperature - Cesaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Applications	Telecom
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Approvals	CE, UR
Mounting Type Through Hole Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Operating Temperature	-
Package / Case Radial Bend Cylinder Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.562" Dia x 0.944" L (14.28mm x 23.98mm)	Mounting Type	Through Hole
` '	Package / Case	Radial Bend Cylinder
Report errors?	Size / Dimension	0.562" Dia x 0.944" L (14.28mm x 23.98mm)
		Report errors?

0TLS040.TXLS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0TLS040.TXLS Payment Methods





















0TLS040.TXLS Shipping Methods













If you have any question about OTLS040.TXLS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com