



# **OTLS050.TXLB Information**

Heisener.com

Part NumberOTLS050.TXLBManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 50A 170VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0TLS050.TXLB Specifications**

Manufacturer Part Number         OTLS050.TXLB           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cylindrical, Blade Terminal (Bolt)           Series         POWR-GARD? TLS           Fuse Type         Cartridge           Current Rating         50A           Voltage Rating - AC         -           Voltage Rating - DC         170V           Response Time         Fast           Applications         Telecom           Features         -           Class         -           Approvals         CE, UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         100kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         0.563" Dia x 1.580" L (14.30mm x 40.13mm)    Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? TLSFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Manufacturer Part Number	0TLS050.TXLB
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? TLS Fuse Type Cartridge Current Rating SoA Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Features - Class - Approvals Cye, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Specialty Fuses Soa Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Specialty Fuses Soa Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Specialty Fuses Soa Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Specialty	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Category	Circuit Protection
SeriesPOWR-GARD? TLSFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.580" L (14.30mm x 40.13mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating50AVoltage Rating - AC-Voltage Rating - DC170VResponse TimeFastApplicationsTelecomFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Telecom  Features  - Class  - Approvals  CE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  50A  170V  170V  170V  1804	Series	POWR-GARD? TLS
Voltage Rating - AC  Voltage Rating - DC  170V  Response Time Fast  Applications Telecom  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  - Class Class CE, UR COLORA  CE, UR COLORA  C	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Telecom  Features - Class - Approvals Ce, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  170V  Fast  Fast  CE, UR  CE, UR  100kA  Bolt Mount  Cylindrical, Blade Terminal (Bolt) Size / Dimension  170V  Fast  Fast  Fast  Fast  Cylindrical, Blade Terminal (Bolt)  0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Current Rating	50A
Response Time Applications Telecom Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Telecom Ce, UR CE, UR CE, UR COBMA Bolt Mount CE, UR COBMA Bolt Mount CE, UR COBMA	Voltage Rating - AC	-
Applications Features - Class - Approvals Ce, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Telecom  CE, UR  CE, UR  CE, UR  Cylindrical, Blade Terminal (Bolt) 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Voltage Rating - DC	170V
Features - Class - Class - CE, UR  Operating Temperature - CE, UR  Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Applications	Telecom
Approvals  CE, UR  Operating Temperature  - Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  100kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Approvals	CE, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 0.563" Dia x 1.580" L (14.30mm x 40.13mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.563" Dia x 1.580" L (14.30mm x 40.13mm)
		Report errors?

#### **0TLS050.TXLB Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **0TLS050.TXLB Payment Methods**



















### **0TLS050.TXLB Shipping Methods**













If you have any question about 0TLS050.TXLB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com