



0ZCE0075FF2E Information



For Reference Only

Part Number 0ZCE0075FF2E

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESTTBLE 0.75A 6V CHIP 0805

Package 0805 (2012 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZCE0075FF2E Specifications

Manufacturer Part Number OZCE0075FF2E Manufacturer Bel Fuse Inc. Category Circuit Protection Package 0805 (2012 Metric), Concave Series 0ZCE Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (lh) (Max) 750mA Current - Trip (lt) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing - Report errors?		
Category Circuit Protection Package 0805 (2012 Metric), Concave Series 0ZCE Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Manufacturer Part Number	0ZCE0075FF2E
Package 0805 (2012 Metric), Concave Series OZCE Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (lh) (Max) 750mA Current - Trip (lt) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Manufacturer	Bel Fuse Inc.
Package 0805 (2012 Metric), Concave Series 0ZCE Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Category	Circuit Protection
Series OZCE Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 6V Current - Max 40A Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Package	0805 (2012 Metric), Concave
Voltage - Max 6V Current - Max 40A Current - Hold (lh) (Max) 750mA Current - Trip (lt) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Series	0ZCE
Current - Max 40A Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Type	Polymeric
Current - Hold (Ih) (Max) 750mA Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Voltage - Max	6V
Current - Trip (It) 1.5A Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Current - Max	40A
Time to Trip 200ms Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Current - Hold (Ih) (Max)	750mA
Resistance - Initial (Ri) (Min) 90 mOhms Resistance - Post Trip (R1) (Max) 350 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Current - Trip (It)	1.5A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing - 350 mOhms -40°C ~ 85°C -40°C ~ 85°C	Time to Trip	200ms
Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	90 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	350 mOhms
Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Resistance - 25°C (Typ)	-
Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C
Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Ratings	-
Size / Dimension 0.083" L x 0.053" W (2.10mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.049" (1.25mm) -	Package / Case	0805 (2012 Metric), Concave
Thickness (Max) 0.049" (1.25mm) Lead Spacing -	Size / Dimension	0.083" L x 0.053" W (2.10mm x 1.35mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.049" (1.25mm)
Report errors?	Lead Spacing	-
		Report errors?

0ZCE0075FF2E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZCE0075FF2E Payment Methods



















0ZCE0075FF2E Shipping Methods













If you have any question about 0ZCE0075FF2E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com