

**0ZCF0030FF2C Information**


For Reference Only

**Part Number** [0ZCF0030FF2C](#)  
**Manufacturer** Bel Fuse Inc.  
**Category** Circuit Protection  
[PTC Resettable Fuses](#)  
**Description** PTC RESETTABLE 60V 300MA 2920  
**Package** 2920 (7351 Metric), Concave  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**0ZCF0030FF2C Specifications**

Manufacturer Part Number	<a href="#">0ZCF0030FF2C</a>
Manufacturer	Bel Fuse Inc.
Category	Circuit Protection <a href="#">PTC Resettable Fuses</a>
Package	2920 (7351 Metric), Concave
Series	0ZCF
Type	Polymeric
Voltage - Max	60V
Current - Max	100A
Current - Hold (Ih) (Max)	300mA
Current - Trip (It)	600mA
Time to Trip	3s
Resistance - Initial (Ri) (Min)	1 Ohms
Resistance - Post Trip (R1) (Max)	4.8 Ohms
Resistance - 25°C (Typ)	-
Operating Temperature	-40°C ~ 85°C
Ratings	-
Mounting Type	Surface Mount
Package / Case	2920 (7351 Metric), Concave
Size / Dimension	0.290" L x 0.202" W (7.36mm x 5.12mm)
Height - Seated (Max)	-
Thickness (Max)	0.045" (1.15mm)
Lead Spacing	-

[Report errors?](#)

## 0ZCF0030FF2C Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0ZCF0030FF2C Payment Methods



## 0ZCF0030FF2C Shipping Methods



If you have any question about 0ZCF0030FF2C, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)