



0ZCG0020AF2C Information

Category

Part Number 0ZCG0020AF2C Manufacturer Bel Fuse Inc. Circuit Protection PTC Resettable Fuses

Description PTC RESTTBLE 0.20A 60V CHIP 1812

Package 1812 (4532 Metric), Concave

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZCG0020AF2C Specifications

Manufacturer Part Number OZCG0020AF2C Manufacturer Bel Fuse Inc. Category Circuit Protection Package 1812 (4532 Metric), Concave Series 0ZCG Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave Size / Dimension 0.179" L x 0.128" W (4.55mm x 3.24mm)		
Category Circuit Protection PTC Resettable Fuses Package 1812 (4532 Metric), Concave Series 0ZCG Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Manufacturer Part Number	0ZCG0020AF2C
Package 1812 (4532 Metric), Concave Series 0ZCG Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Manufacturer	Bel Fuse Inc.
Package 1812 (4532 Metric), Concave Series 0ZCG Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (lh) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Category	Circuit Protection
Series OZCG Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave		PTC Resettable Fuses
Type Polymeric Voltage - Max 60V Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - 40°C ~ 85°C Ratings - 40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Package	1812 (4532 Metric), Concave
Voltage - Max Current - Max 40A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Series	0ZCG
Current - Max Current - Hold (Ih) (Max) 200mA Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Type	Polymeric
Current - Hold (Ih) (Max) Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Voltage - Max	60V
Current - Trip (It) 400mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 800 mOhms Resistance - Post Trip (R1) (Max) 5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Current - Max	40A
Time to Trip Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 20ms 20ms 20ms 800 mOhms 5 Ohms - Commonthering Surface Mount 1812 (4532 Metric), Concave	Current - Hold (Ih) (Max)	200mA
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) So Ohms Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Current - Trip (It)	400mA
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Time to Trip	20ms
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Resistance - Initial (Ri) (Min)	800 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Resistance - Post Trip (R1) (Max)	5 Ohms
Ratings - Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Resistance - 25°C (Typ)	-
Mounting Type Surface Mount Package / Case 1812 (4532 Metric), Concave	Operating Temperature	-40°C ~ 85°C
Package / Case 1812 (4532 Metric), Concave	Ratings	-
	Mounting Type	Surface Mount
Size / Dimension 0.179" L x 0.128" W (4.55mm x 3.24mm)	Package / Case	1812 (4532 Metric), Concave
	Size / Dimension	0.179" L x 0.128" W (4.55mm x 3.24mm)
Height - Seated (Max)	Height - Seated (Max)	-
Thickness (Max) 0.035" (0.90mm)	Thickness (Max)	0.035" (0.90mm)
Lead Spacing -	Lead Spacing	-
Report errors?		Report errors?

0ZCG0020AF2C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZCG0020AF2C Payment Methods



















0ZCG0020AF2C Shipping Methods













If you have any question about 0ZCG0020AF2C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com