

**0ZCG0260BF2B Information**


For Reference Only

**Part Number** [0ZCG0260BF2B](#)  
**Manufacturer** Bel Fuse Inc.  
**Category** Circuit Protection  
[PTC Resettable Fuses](#)  
**Description** PTC RESTTBLE 2.6A 16V CHIP 1812  
**Package** 1812 (4532 Metric), Concave  
 For the pricing/inventory/lead time, please contact us  
 Website: <https://www.heisener.com>  
 E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)


[Request a Quote](#)
**Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.


**0ZCG0260BF2B Specifications**

Manufacturer Part Number	<a href="#">0ZCG0260BF2B</a>
Manufacturer	Bel Fuse Inc.
Category	Circuit Protection <a href="#">PTC Resettable Fuses</a>
Package	1812 (4532 Metric), Concave
Series	0ZCG
Type	Polymeric
Voltage - Max	16V
Current - Max	100A
Current - Hold (Ih) (Max)	2.6A
Current - Trip (It)	5A
Time to Trip	5s
Resistance - Initial (Ri) (Min)	15 mOhms
Resistance - Post Trip (R1) (Max)	50 mOhms
Resistance - 25°C (Typ)	-
Operating Temperature	-40°C ~ 85°C
Ratings	-
Mounting Type	Surface Mount
Package / Case	1812 (4532 Metric), Concave
Size / Dimension	0.179" L x 0.128" W (4.55mm x 3.24mm)
Height - Seated (Max)	-
Thickness (Max)	0.061" (1.55mm)
Lead Spacing	-

[Report errors?](#)

## 0ZCG0260BF2B Guarantees



### Quality Guarantees

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 0ZCG0260BF2B Payment Methods



## 0ZCG0260BF2B Shipping Methods



If you have any question about 0ZCG0260BF2B, please do not hesitate to contact us!

Website: <https://www.heisener.com>

E-mail: [salesdept@heisener.com](mailto:salesdept@heisener.com)