




0ZCJ0100FF2E Information



For Reference Only

Part Number 0ZCJ0100FF2E

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESTTBLE 1.0A 6V CHIP 1206

Package 1206 (3216 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZCJ0100FF2E Specifications

Manufacturer Part Number OZCJ0100FF2E Manufacturer Bel Fuse Inc. Category Circuit Protection Package 1206 (3216 Metric), Concave Scries 0ZCJ Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (lh) (Max) 1A Current - Trip (lt) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C - 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing - Report errors?	•	
Category Circuit Protection Package 1206 (3216 Metric), Concave Series OZCJ Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (Ih) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer Part Number	0ZCJ0100FF2E
Package 1206 (3216 Metric), Concave Series 0ZCJ Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (Ih) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer	Bel Fuse Inc.
Package 1206 (3216 Metric), Concave Series 0ZCJ Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (lh) (Max) 1A Current - Trip (lt) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Category	Circuit Protection
Series OZCJ Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (Ih) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 6V Current - Max 100A Current - Hold (lh) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Package	1206 (3216 Metric), Concave
Voltage - Max 6V Current - Max 100A Current - Hold (lh) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Series	0ZCJ
Current - Max 100A Current - Hold (Ih) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Туре	Polymeric
Current - Hold (Ih) (Max) 1A Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Voltage - Max	6V
Current - Trip (It) 1.8A Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Max	100A
Time to Trip 300ms Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Hold (Ih) (Max)	1A
Resistance - Initial (Ri) (Min) 55 mOhms Resistance - Post Trip (R1) (Max) 210 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Trip (It)	1.8A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing - 210 mOhms - 0.40°C ~ 85°C -40°C ~	Time to Trip	300ms
Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	55 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	210 mOhms
Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - 25°C (Typ)	-
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C
Package / Case 1206 (3216 Metric), Concave Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Ratings	-
Size / Dimension 0.128" L x 0.065" W (3.25mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.039" (1.00mm) -	Package / Case	1206 (3216 Metric), Concave
Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Size / Dimension	0.128" L x 0.065" W (3.25mm x 1.65mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.039" (1.00mm)
Report errors?	Lead Spacing	-
		Report errors?

0ZCJ0100FF2E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZCJ0100FF2E Payment Methods



















0ZCJ0100FF2E Shipping Methods













If you have any question about 0ZCJ0100FF2E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com