




0ZCK0010FF2G Information



For Reference Only

Part Number 0ZCK0010FF2G

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESTTBLE 0.10A 15V CHIP 0805

Package 0805 (2012 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZCK0010FF2G Specifications

Series OZCK Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -			
Category Circuit Protection PTC Resettable Fuses Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer Part Number	0ZCK0010FF2G	
Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer	Bel Fuse Inc.	
Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (lh) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Category	Circuit Protection	
Series 0ZCK Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -		PTC Resettable Fuses	
Type Polymeric Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Package	0805 (2012 Metric), Concave	
Voltage - Max 15V Current - Max 100A Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Series	0ZCK	
Current - Max 100A Current - Hold (lh) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Туре	Polymeric	
Current - Hold (Ih) (Max) 100mA Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Voltage - Max	15V	
Current - Trip (It) 300mA Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Max	100A	
Time to Trip 1.5s Resistance - Initial (Ri) (Min) 700 mOhms Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Hold (Ih) (Max)	100mA	
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Trip (It)	300mA	
Resistance - Post Trip (R1) (Max) 6 Ohms Resistance - 25°C (Typ)	Time to Trip	1.5s	
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	700 mOhms	
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	6 Ohms	
Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - 25°C (Typ)	-	
Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C	
Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Ratings	-	
Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Mounting Type	Surface Mount	
Height - Seated (Max) Thickness (Max) Lead Spacing - 0.039" (1.00mm) -	Package / Case	0805 (2012 Metric), Concave	
Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Size / Dimension	0.085" L x 0.053" W (2.15mm x 1.35mm)	
Lead Spacing -	Height - Seated (Max)	-	
	Thickness (Max)	0.039" (1.00mm)	
D (0	Lead Spacing	-	
Report errors?		Report	errors?

0ZCK0010FF2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZCK0010FF2G Payment Methods



















0ZCK0010FF2G Shipping Methods













If you have any question about 0ZCK0010FF2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com