




0ZCK0020FF2G Information



For Reference Only

Part Number 0ZCK0020FF2G

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESTTBLE 0.20A 9V CHIP 0805

Package 0805 (2012 Metric), Concave

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZCK0020FF2G Specifications

Manufacturer Part Number OZCK0020FF2G Manufacturer Bel Fuse Inc. Category Circuit Protection Package 0805 (2012 Metric), Concave Scries 0ZCK Type Polymeric Voltage - Max 100A Current - Max 100A Current - Hold (lh) (Max) 200mA Current - Trip (lt) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C - 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing - Report errors?	.	
Category Circuit Protection Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 9V Current - Max 100A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer Part Number	0ZCK0020FF2G
Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 9V Current - Max 100A Current - Hold (lh) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Manufacturer	Bel Fuse Inc.
Package 0805 (2012 Metric), Concave Series 0ZCK Type Polymeric Voltage - Max 9V Current - Max 100A Current - Hold (lh) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Category	Circuit Protection
Series 0ZCK Type Polymeric Voltage - Max 9V Current - Max 100A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -		PTC Resettable Fuses
Type Polymeric Voltage - Max 9V Current - Max 100A Current - Hold (lh) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Package	0805 (2012 Metric), Concave
Voltage - Max 9V Current - Max 100A Current - Hold (lh) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Series	0ZCK
Current - Max 100A Current - Hold (Ih) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Туре	Polymeric
Current - Hold (Ih) (Max) 200mA Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Voltage - Max	9V
Current - Trip (It) 500mA Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Max	100A
Time to Trip 20ms Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Hold (Ih) (Max)	200mA
Resistance - Initial (Ri) (Min) 400 mOhms Resistance - Post Trip (R1) (Max) 3.5 Ohms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Current - Trip (It)	500mA
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing - 3.5 Ohms - - 0.085°C - 0.00000000000000000000000000000000	Time to Trip	20ms
Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	400 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	3.5 Ohms
Ratings - Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Resistance - 25°C (Typ)	-
Mounting Type Surface Mount Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C
Package / Case 0805 (2012 Metric), Concave Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Ratings	-
Size / Dimension 0.085" L x 0.053" W (2.15mm x 1.35mm) Height - Seated (Max) - Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Mounting Type	Surface Mount
Height - Seated (Max) Thickness (Max) Lead Spacing - - - 0.039" (1.00mm) -	Package / Case	0805 (2012 Metric), Concave
Thickness (Max) 0.039" (1.00mm) Lead Spacing -	Size / Dimension	0.085" L x 0.053" W (2.15mm x 1.35mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.039" (1.00mm)
Report errors?	Lead Spacing	-
		Report errors?

0ZCK0020FF2G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZCK0020FF2G Payment Methods



















0ZCK0020FF2G Shipping Methods













If you have any question about 0ZCK0020FF2G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com