



0ZRB0300FF2B Information

Heisener.com

Part NumberOZRB0300FF2BManufacturerBel Fuse Inc.CategoryCircuit Protection
PTC Resettable Fuses

Description PTC RESETTABLE 30V 3.00A RADIAL

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZRB0300FF2B Specifications

Manufacturer Part Number OZRB0300FF2B Manufacturer Bel Fuse Inc. Category Circuit Protection Package Radial, Disc Series OZRB Type Polymeric Voltage - Max 40A Current - Max 40A Current - Hold (lh) (Max) 3A Current - Trip (lt) 6A Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm) Report errors?	•	
Category Circuit Protection Package Radial, Disc Series OZRB Type Polymeric Voltage - Max 30V Current - Max 40A Current - Hold (Ih) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature 40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449° L x 0.118° W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Manufacturer Part Number	0ZRB0300FF2B
Package Radial, Disc Series 0ZRB Type Polymeric Voltage - Max 30V Current - Max 40A Current - Hold (lh) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Manufacturer	Bel Fuse Inc.
Package Radial, Disc Series OZRB Type Polymeric Voltage - Max 30V Current - Max 40A Current - Hold (lh) (Max) 3A Current - Trip (lt) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Category	Circuit Protection
Series OZRB Type Polymeric Voltage - Max 30V Current - Max 40A Current - Hold (Ih) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)		PTC Resettable Fuses
Type Polymeric Voltage - Max 30V Current - Max 40A Current - Hold (lh) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Package	Radial, Disc
Voltage - Max 30V Current - Max 40A Current - Hold (lh) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Series	0ZRB
Current - Max 40A Current - Hold (Ih) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Туре	Polymeric
Current - Hold (Ih) (Max) 3A Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Voltage - Max	30V
Current - Trip (It) 6A Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Current - Max	40A
Time to Trip 10.8s Resistance - Initial (Ri) (Min) 20 mOhms Resistance - Post Trip (R1) (Max) 80 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Current - Hold (Ih) (Max)	3A
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Current - Trip (It)	6A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Time to Trip	10.8s
Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - Initial (Ri) (Min)	20 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - Post Trip (R1) (Max)	80 mOhms
Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - 25°C (Typ)	-
Mounting Type Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) Lead Spacing 0.201" (5.10mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Radial, Disc Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Ratings	-
Size / Dimension 0.449" L x 0.118" W (11.40mm x 3.00mm) Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.681" (17.30mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Package / Case	Radial, Disc
Thickness (Max) Lead Spacing 0.201" (5.10mm)	Size / Dimension	0.449" L x 0.118" W (11.40mm x 3.00mm)
Lead Spacing 0.201" (5.10mm)	Height - Seated (Max)	0.681" (17.30mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.201" (5.10mm)
		Report errors?

0ZRB0300FF2B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZRB0300FF2B Payment Methods



















0ZRB0300FF2B Shipping Methods













If you have any question about 0ZRB0300FF2B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com