

## 1-1393816-3 Information

Heisener.com

**Part Number** 1-1393816-3

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPST 5A 110V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1-1393816-3 Specifications

Manufacturer Part Number         1-1393816-3           Manufacturer         TE Connectivity Potter & Brumfield Relays           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         V23005, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         34.4mA           Coil Voltage         110VAC           Contact Form         DPST-NO/NC (1 Form A and B)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         V23005, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         34.4mA           Coil Voltage         110VAC           Contact Form         DPST-NO/NC (1 Form A and B)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer Part Number	1-1393816-3
Package         -           Series         V23005, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         34.4mA           Coil Voltage         110VAC           Contact Form         DPST-NO/NC (1 Form A and B)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         V23005, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         34.4mA           Coil Voltage         110VAC           Contact Form         DPST-NO/NC (1 Form A and B)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
Series         V23005, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         34.4mA           Coil Voltage         110VAC           Contact Form         DPST-NO/NC (1 Form A and B)           Contact Rating (Current)         5A           Switching Voltage         250VAC, 250VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         -           Operate Time         -           Release Time         -           Features         -           Mounting Type         Socketable           Termination Style         Plug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current34.4mACoil Voltage110VACContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 34.4mA Coil Voltage 110VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Series	V23005, AXICOM
Coil Current Coil Voltage 110VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time Release Time - Features - Mounting Type Socketable Termination Style 110VAC  DPST-NO/NC (1 Form A and B)	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Release Time - Hounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B)  Contact Rating (Current) 5A  Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable  Termination Style Plug In	Coil Current	34.4mA
Contact Rating (Current)  Switching Voltage  250VAC, 250VDC - Max  Turn On Voltage (Max)  88 VAC  Turn Off Voltage (Min)  Operate Time  - Release Time  - Features  Mounting Type  Socketable  Termination Style  5A  250VAC, 250VDC - Max  88 VAC  -  88 VAC  -  88 VAC  -  9	Coil Voltage	110VAC
Switching Voltage 250VAC, 250VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable  Termination Style Plug In	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  -  Retures  Mounting Type  Socketable  Termination Style  88 VAC  -  88 VAC  -  88 VAC  -  Pug In	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 250VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	88 VAC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

### 1-1393816-3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **1-1393816-3 Payment Methods**

































If you have any question about 1-1393816-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com