

1-1415535-1 Information

Heisener.com

Part Number 1-1415535-1

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 4PDT 6A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1-1415535-1 Specifications

Manufacturer Part Number 1-1415535-1 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series PT, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesPT, SCHRACKRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time-Release Time-FeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeDIN RailTermination StyleScrew Terminal	Manufacturer Part Number	1-1415535-1
Package - Series PT, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series PT, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Category	Relays
SeriesPT, SCHRACKRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current-Coil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)6ASwitching Voltage240VAC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time-Release Time-FeaturesLED Indicator, Mechanical Indicator, Test ButtonMounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose with Socket Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Serew Terminal	Package	-
Coil Type Non Latching Coil Current - Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Series	PT, SCHRACK
Coil Current Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style	Relay Type	General Purpose with Socket
Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 6A Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Coil Current	-
Contact Rating (Current) Switching Voltage 240VAC - Max 19.2 VAC Turn On Voltage (Max) 7.2 VAC Operate Time Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style 6A 240VAC - Max 19.2 VAC - 19.3 VAC - 19.4 VAC - 19.5 VAC - 19.6 VAC 19.7 VAC - 19.8 VAC - 19.9 VAC - 1	Coil Voltage	24VAC
Switching Voltage 240VAC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Contact Rating (Current)	6A
Turn Off Voltage (Min) 7.2 VAC Operate Time - Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	240VAC - Max
Operate Time - Release Time - LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Screw Terminal	Turn On Voltage (Max)	19.2 VAC
Release Time - Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	7.2 VAC
Features LED Indicator, Mechanical Indicator, Test Button Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	-
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	-
Termination Style Screw Terminal	Features	LED Indicator, Mechanical Indicator, Test Button
	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

1-1415535-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1-1415535-1 Payment Methods





















1-1415535-1 Shipping Methods













If you have any question about 1-1415535-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com